

# Data Sheet – SAV230 Hi Block Gloss

**100 GLOSS WHITE PVC / GREY PERM PSA /100GLOSS WHITE PVC/ CLEAR PERM PSA /135gsm PE KRAFT LINER**

## General

SAV230 is a smooth glossy white PVC laminated with a permanent, low shrinkage, grey acrylic adhesive. The PVC is suitable for printing by Latex, UV, Solvent and Eco-Solvent based inks. The glossy finish gives excellent print finish with vibrant colours. The middle block out layer gives this product a good level of opacity. Mainly for use on windows applications, however can be used on walls. The high opacity ensures that the print will not be visible from the other side of glass window. This product can be used with a transparent window film on the reverse side to create double-sided window graphics. The PE coated release ensures product stability against moisture.

TYPICAL AVAILABLE WIDTHS: 1370mm; 1520mm

## Product Features and Performance Data.

<u>Component</u>	<u>Description</u>	<u>Details</u>	<u>Gauge (Microns)</u>	<u>Tolerance</u>
A	Glossy White PVC.	Smooth, Monomeric Plastisized	100	+/- 10
B	Permanent BLOCKOUT Adhesive.	Exhibiting good Tack and Peel Adhesion.	35	+/- 2
C	Glossy White PVC	Smooth, Monomeric Plastisized	100	+/- 10
D	Clear Permanent Adhesive.	Exhibiting good Tack and Peel Adhesion.	35	+/- 2
E	White, Kraft, Clay Coated release liner.	135 gsm, standard release, Siliconised one side.	145	+/- 10

**APPLICATION TEMP: +10°C – +40°C SERVICE TEMP: -20°C – +70°C SHELF LIFE: 1 YEAR**

**STORAGE:** Effort must be made to keep this product free from moisture and excessive exposure to ultra violet radiation before use.

The data above does not constitute a guaranteed specification and is given in good faith. End users of this product are urged to test the product and the substrates concerned, in the specific application and exposure conditions in which the product will be utilised.