



+44 (0)1928 599910
sales@aquabond.co.uk
Unit 5a Christleton Court
Manor Park, Runcorn
Cheshire, WA7 1ST

Data Sheet – AQUA WINDOW-FILM

CHEMICAL TREATMENT – 36/50 GLOSS CLEAR POLYESTER FILM – 2 side treated

General

Aqua Window Film is made up of a single layer of low haze clear polyester which has been chemically treated on both sides for adhesion enhancement for various inks and adhesives. This product is available in 36 & 50 microns and is used to make 'windows' for envelopes and in documents. This product is suitable for use on 'forms' machines such as a Tamarack.

NOMINAL MASTER WIDTH: 1000mm USABLE

AVAILABLE REEL LENGTHS: 1000m , 1500m & 2000m

TYPICAL AVAILABLE WIDTHS: 50mm UP TO 1000mm (ALL WIDTHS TAKEN FROM A 1000mm MASTER WIDTH)

MINIMUM ORDER QUANTITIE: 1000m²

STORAGE: Effort must be made to keep this product free from moisture and excessive exposure to ultra violet radiation before use.

The data above does not constitute a guaranteed specification and is given in good faith. End users of this product are urged to test the product and the substrates concerned, in the specific application and exposure conditions in which the product will be utilised.